

<b>Characteristics</b>	Luxury RigidCore Plank Floating Floor with IXPE Underlayment and 5G Superior Click System 20 Mil WearLayer
<b>Description</b>	Plank Size 7" Wide x 48" Long (Registered & Embossed)
<b>Size/Thickness</b>	5.0mm Total Thickness (4.0 Core + 1.0mm IXPE + 12mm Wearlayer)
<b>Installation</b>	2G Click System - Floating
<b>Warranty</b>	Lifetime Structural Warranty 10-Yr Limited Light Commercial Warranty
<b>Wear Resistance (EN13329)</b>	≥ 4000mm - Classification (Class 34)
<b>Impact Resistance (EN13329)</b>	≥ 1800mm - Classification (Class 34)
<b>Micro-Scratch Resistance</b>	ISO 1518-1: ≥ 3200g
<b>Static Load Limit</b>	ASTM F970 - 15, Class 4 Heavy Commercial
<b>Impact Sound Reduction (IIC)</b>	IIC: 59
<b>Locking Strength</b>	Long side ≥ 6.3kn/m; Short side ≥ 5.4kn/m
<b>Stain Resistance</b>	No visible change with 10-min. duration of contact (water, acetone, cleaning solution, coffee, sodium hydroxide (NaOH), hydrogen peroxide (H <sub>2</sub> O <sub>2</sub> ), shoe polish.
<b>Fire Resistance</b>	ASTM E648/662 - 1.09 W/cm <sup>2</sup> - Class 1
<b>Fungi Resistance (ASTM G21-15)</b>	Unlike cork, this project shows zero "none" results for observed growth.
<b>FloorScore®</b>	SCS-FS-04026   2016.06.01 - 2017.05.31
<b>Content of Box</b>	7" x48" - 23.64 Sq.Ft./Carton
<b>Content of Pallet</b>	55 cartons 1300.2 Sq.Ft./ Pallet