

◆ Specifications ◆

CLASSIFICATION	ASTM F-3261-17 Resilient flooring in modular format with Solid Polymeric Core
SIZE	7" x 48" / 183 mm x 1220 mm (nom)
OVERALL THICKNESS	0.18" / 4.5 mm (nom) (3.5 mm + 1 mm cushion backing)
WEAR LAYER	12 mil / 0.30 mm featuring <i>Tuff Shield</i> finish
CONSTRUCTION	ABA SPC
EDGE	Bevel
STANDARD COLORS	8 standard colors
INSTALLATION METHOD	Angle/Angle
WEAR LIMITED WARRANTY	30-Year Residential / 20-Year Light Commercial
RECYCLED CONTENT	This product contains no recycled content. 100% recyclable post-use.

PRODUCT TESTING

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-17	Class I, CRF >1.13
Dimensional Stability	ASTM 2199	Passed
Residual Indentation	ASTM F 1914	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662	Passed
Static Load Limit	ASTM F 970	Passed
Slip Resistance	ASTM C 1028	Passed

