

◆ Specifications ◆

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 177.8 mm x 1219.2 mm (Plank) 18" x 18" / 457.2 mm x 457.2 mm (Tile)
Overall Thickness*	0.08" / 2.0 mm
Wear Layer	12 mil / 0.30 mm
Edge	Square
Standard Colors	6 standard planks / 2 standard tiles
Installation Method	Glue Down
Wear Limited Warranty	30 Year Residential / 20-Year Light Commercial
Recycled Content	This product contains 50% recycled content. 100% recyclable post-use

Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
+STC Sound Testing	ASTM E 492-09	+STC 61
+IIC Sound Testing	ASTM E 989-06	+IIC 64
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed

