

◆ Specifications ◆

CLASSIFICATION	ASTM F-3261-17 Resilient flooring in modular format with Solid Polymeric Core
SIZE	7" x 48" / 183 mm x 1220 mm (nom)
OVERALL THICKNESS	0.20" / 5.0 mm (nom) (4 mm + 1 mm cushion backing) 20 mil / 0.50 mm featuring
WEAR LAYER	
CONSTRUCTION	ABA SPC
STANDARD COLORS	5 standard colors
INSTALLATION METHOD	Angle/Angle
WEAR LIMITED WARRANTY	Lifetime Residential / 30-Year Commercial
RECYCLED CONTENT	This product contains no recycled content. 100% recyclable post-use.

Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-17	Class I, CRF ≥0.45
Dimensional Stability	ISO 23999	Passed
Residual Indentation	ASTM F 1914	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-15A	Passed
Static Load Limit	ASTM F 970	Passed
Slip Resistance	ASTM C 1028	Passed
*IIC Sound Testing	ASTM E 989-06	*IIC 61

