

Characteristics	Luxury RigidCore Plank Floating Floor with IXPE Underlayment and 2G Superior Click System 12 Mil WearLayer
Description	Plank Size 7" Wide x 48" Long (Wood Grain Texture)
Size/Thickness	4.7mm Total Thickness (3.7mm Core + 1.0mm EVA + 12mil Wearlayer)
Installation	2G Click System - Floating
Warranty	Lifetime Structural Warranty 10-Yr Limited Light Commercial Warranty
Wear Resistance (EN13329)	≥ 4000mm - Classification (Class 34)
Impact Resistance (EN13329)	≥ 1800mm - Classification (Class 34)
Micro-Scratch Resistance	ISO 1518-1: ≥ 3200g
Static Load Limit	ASTM F970 - 15, Class 4 Heavy Commercial
Impact Sound Reduction (IIC)	IIC: 59
Locking Strength	Long side ≥ 6.3kn/m; Short side ≥ 5.4kn/m
Stain Resistance	No visible change with 10-min. duration of contact (water, acetone, cleaning solution, coffee, sodium hydroxide (NaOH), hydrogen peroxide (H ₂ O ₂), shoe polish.
Fire Resistance	ASTM E648/662 - 1.09 W/cm ² - Class 1
Fungi Resistance (ASTM G21-15)	Unlike cork, this project shows zero "none" results for observed growth.
FloorScore®	SCS-FS-04026 2020.06.01 - 2021.05.31
Content of Box	7" x48" - 21.27 Sq.Ft./Carton
Content of Pallet	65 cartons - 2149.50 lbs