

◆ Specifications ◆

REVEILLE PLUS XL

Solid Polymer Core Flooring

CLASSIFICATION	ASTM F-3261-17 Resilient flooring in modular format with Solid Polymeric Core
SIZE	9" x 60" / 230 mm x 1524 mm (nom)
OVERALL THICKNESS	0.20" / 5.0 mm (4 mm + 1 mm cushion backing)
WEAR LAYER	20 mil / 0.50 mm featuring Superior Coating finish
CONSTRUCTION	ABA SPC
EDGE	Bevel
STANDARD COLORS	6 colors
INSTALLATION METHOD	Angle/Angle
WEAR LIMITED WARRANTY	Lifetime Residential / 30 Year Light Commercial
RECYCLED CONTENT	This product contains no recycled content. 100% recyclable post-use.

PACKAGING	30.18 ft ² (2.80 m ²) per carton 8 pieces per carton 56 cartons per pallet
------------------	---



WEIGHT PER CARTON	50.99 lbs / 23.13 kg
--------------------------	----------------------

Coordinating Moldings

PRODUCT TESTING

Chemical Resistance	ASTM F 925	PASS	Resistance to Light	ASTM F 1515	PASS
Critical Radiant Flux	ASTM E 648-17	PASS CLASS 1	Smoke Density	ASTM E 662-15A	PASS
Dimensional Stability	ASTM F 23999	PASS	Static Load Limit	ASTM F 970	PASS
Residual Indentation	ASTM F 1914	PASS	Slip Resistance	ASTM C 1028	PASS
Resistance to Heat	ASTM F 1514	PASS	IIC Sound Testing	ASTM E 989-06	+IIC 61
			STC Sound Testing	ASTM E 413-16	+STC 53



Waterproof | Low Maintenance | Acoustical Attributes | Durable | Hygienic | Pet Friendly | Kid Friendly



*All measurements are nominal. All specifications and offerings are subject to change without notice. Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.